




RG - AP520(DA)

ǎ ǎ è ă è ȳ Ā

ǎ ă Ą æ a Ѧ ȳ ă ă ă



н ã Ľ ъ
Â

а

н è а Â Ю

А и Â А ё Л а А

А а Â

ң Ғ й Â

Ғ ӱ ң Ң Ә Ә ä ä Җ җ
Â Ә з ё Â ң
Â

” ‘ <http://www.ruijie.com.cn/>

” ‘ <http://webchat.ruijie.com.cn>

” Ғ 6 ‘ <http://www.ruijie.com.cn/service.aspx>

” 7 × 24 Ғ ‘ 4008-111-000

” ‘ <http://bbs.ruijie.com.cn/portal.php>

” ‘

1

RG-AP520(DA) ^ AP520(DA)~ ý ı Â

RG-AP520(DA) ı ı ı ı ı ı 50 ° ~70 ° ı

ăăăăăăŁıÂ

1.1 RG-AP520(DA)


2.4G

	—	AP	^	~
√	3Hz 2 2	AP	Æ	AP

ap

	—	AP	∅	/	Â
	3Hz	AP			
	3Hz	AP	ч	Љ	Link down
	3Hz	AP	a	Ю	
	—	AP			
5	16 /min	AP			
	—	AP	^	~	
√	3Hz 2 2	AP	Æ	AP	

1-2



1000BASE-T/100BASE-TX/10BASE-T	PoE	Љ
--------------------------------	-----	---

RG-AP520(DA)	1 Љ	PoE	Â
PoE	802.3af/802.3at		

RG-AP520(DA)	Â

RG-AP520(DA) Ȧ Ȧ Ȧ Ȧ

"			$\dot{\epsilon}$	$\hat{A}$
"	$\mathcal{A}$	RG-AP520(DA) $\downarrow$ $\dot{\epsilon}$		$\hat{A}$
"	$\mathcal{A}$	RG-AP520(DA)	$\mathcal{U}$	$\hat{A}$

RG-AP520(DA)	й	л	а
--------------	---	---	---

№	RG-AP520(DA)	Â	a	ă
---	--------------	---	---	---

H ₂ S	0.006	0.03
Y NO ₂	0.04	0.15
NH ₃	0.05	0.15
Cl ₂	0.01	0.3

2.5.5

„ DC44-57V 0.3A 15W 10 A

„ PoE 802.3af/802.3at PoE A

RG-AP520(DA)

12.95W

a

a PoE

2.5.6 EMI

„ a б л A

„ л л 11 A

2.6

é	ă	ă ă	ă	ă
ж é	ă	ă	ă	
	ă			

2.7


	ă	ă	Âă
--	---	---	----

3

RG-AP520(DA) AP

3 А

3.1



3.2

RG-AP520(DA)

Æ ä ä ѓ

А

ЛЮ ‘

” Л ѓ А

” А

” А

” П А

” А

” А

” ж ж А

3.3

й AP

ы ЛЮ Y ‘

” а А

” А

” А

” Â

” Â

” ă Â

” Â

” ”I IO Â

” a Â

” a Â

” a Â


” Â

3.4

RG-AP520(DA) Ÿ 6 RG-AP520(DA)_bracket Â


z Ÿ Â

3-1 €




^ b~ H AP A y 3 M8 × 40


3-7



z ^ ~ 3-8 3



3-9




3.5 AP

RG-AP520(DA)AP691J

z RG-AP520(DA)

3-101 ^ -60 ° ~



3-11 $\alpha +60^{\circ} \sim$



3-12 $\alpha 0^{\circ} \sim$

$\alpha -60^{\circ} \sim 60^{\circ} \sim$

RG-AP520(DA)

[illegible]

4

4.1

PoE AP Э Â

„ PoE AP Â

„ √ AP б AC Â

„ PC б AP PC PoE Â

4.2

„ Â

„ б AP Â

Э Ю Л

„ AP Э AC ~ Â

„ AP Â


5

5.1

RG-AP520(DA)	1 7	Â
” ‘ AP	Â	
” ‘ AP	7 Link down	Â
” ‘ AP	CAPWAP	Â
” ‘ AP	a IO	Â
” ‘ AP	CAPWAP	Â
” 5 16 /min’ AP	CAPWAP	Â
” ‘ AP	Â	
” 2 2 ‘ AP	Â	

6

6.1



6.2

„ PoE “ PoE 802.11af ЛА А

” “ А

ЛА ЛА 3

А

AP

1) А

1) ЛА А

z AP Â

z б AP Â

, лб Э, лб Â

Э , Â Â
' 1 Ÿ л Â


Э л , Â
Â ' а а Â 10† лб Ÿ
л Â

CAPWAP , а s AP б AC
AC лб џ Â

A —

1000BASE-T/100BASE-TX/10BASE-T

1000BASE-T/100BASE-TX/10BASE-T	Б	Б	Ю	MDI/MDIX	Crossover		
1000BASE-T	IEEE 802.3ab	100-ohm 5	5	↓	UTP	↓	STP
1000BASE-T	4	4	Э	1000BASE-T	↓	Ю	
A-1 1000BASE-T	↓						





A-2 100BASE-TX/10BASE-T

Pin		
1	Input Receive Data+	Output Transmit Data+
2	Input Receive Data-	Output Transmit Data-
3	Output Transmit Data+	Input Receive Data+
6	Output Transmit Data-	Input Receive Data-
4 à 5 à 7 à 8	Not Used	Not Used

100BASE-TX/10BASE-T

A-3 100BASE-TX/10BASE-T

√



RG-AP520(DA)										Э	Э	Ю	А
^	ä	ä	^ a	Æ	~	Э	Ю	А	~ А	ÿ			
”	ä	ä				è	й	5	ЛЭ’				
	й	7	ЛЭ А										
”			è	й	7	ЛЭ’				й	10		
	ЛЭ А												
”	^	SFP+	~ è	й	5	ЛЭ				й	10		
	ЛЭ А												
”					Æ	Э А							
”			ä	a	ä	А	D-1	А					
D-1	^	~											
”	a	^	ä	ä	~	↑	ä	a	А		л		
	√	√	А		б		a	30mm А					
”		√	”I		А								
”		é	”I	ä	↑			А					
”	√		a	ч	ч	ЛЭ		А					
”				↑	↑	a	А	D-2	А				

D-2

 $\hat{Y}^{\sim}$

"

 $\hat{A}$

D-3

 $\hat{A}$ $\hat{A}$

a

4

 $\mathcal{L}_G$

H,

D-3

 $\hat{b}^{\sim}$

"

a

†

3

Æ Э Â

 $\mathcal{A}$

a

a

H, a

 $\mathcal{A}$ $\hat{A}$

22

220V

à -48V

a

 $\mathfrak{E} \hat{A}$

"

 $\mathcal{P}_G$

4

,

 $\mathcal{A}$

a

ă

 α $\hat{A}$

"

” $\mathcal{L}$ $\mathcal{V}$ $\mathcal{E}$ $\mathfrak{H}$,

” $\hat{A}$

” $\mathfrak{a}$ $\mathfrak{a}$ $\hat{A}$

” $\mathcal{Y}$ $\hat{A}$

" a Â

" ^ ~ | a Â